

FASTIGHETS-FILM



Stainless Steel 10 HC

SPUTTRAD METALL

Fakta:

Transmission synligt ljus (VLT)	9%
Reflektion synligt ljus (VLR)	43%
Bländningsreduktion	90%
Solfaktor (SF)	0.28
UV-reduktion (300-380 nm)	98%
Total värmereduktion (T _{SER})	76%
Tjocklek på film	2 mil/0,05 mm

Key Features:

- Removes up to 98% of Ultra Violet Radiation, reducing fading of fabrics, furnishing and fixtures.
- Scratch resistant coating (Durogard®) for long life and ease of cleaning.
- Ideal for office and most commercial applications.
- Provides two way mirror type privacy during day light hours.
- Improves productivity in workplace by cutting excessive solar heat.
- Reduces glare to ease eyestrain.
- Pressure sensitive adhesive with lower visual distortion and provides good optical clarity.



Montagerekommendation

HC
insides
montage

Enkelglas	Kopplade	2-glas isoler	3-glas isoler
Invändigt	Mellanglas	Ej	Ej

GARANTI: Bekaert ger 10 års fabriksgaranti på den insides installerade fastighetsfilmen (HC) och 3 år på den utsides monterade fastighetsfilmen (OSW) på vertikala glasytor.

FASTIGHETS-FILM



Stainless Steel 20 HC/OSW

SPUTTRAD METALL

Fakta:

Transmission synligt ljus (VLT)	23%
Reflektion synligt ljus (VLR)	28%
Bländningsreduktion	74%
Solfaktor (SF)	0.43
UV-reduktion (300-380 nm)	98%
Total solenergireduktion (T _{SER})	63%
Tjocklek på film	2 mil/0,05 mm

Key Features:

- Removes up to 98% of Ultra Violet Radiation, reducing fading of fabrics, furnishing and fixtures.
- Scratch resistant coating (Durogard®) for long life and ease of cleaning.
- Ideal for office and most commercial applications.
- Provides two way mirror type privacy during day light hours.
- Improves productivity in workplace by cutting excessive solar heat.
- Reduces glare to ease eyestrain.
- Pressure sensitive adhesive with lower visual distortion and provides good optical clarity.



Montagerekommendation

HC
insides
montage

Enkelglas	Kopplade	2-glas isoler	3-glas isoler
Invändigt	Mellanglas	Ej	Ej

OSW
utsides
montage

Enkelglas	Kopplade	2-glas isoler	3-glas isoler
Utvändigt	Utvändigt	Utvändigt	Utvändigt

GARANTI: Bekaert ger 10 års fabriksgaranti på den insides installerade fastighetsfilmen (HC) och 3 år på den utsides monterade fastighetsfilmen (OSW) på vertikala glasytor.

FASTIGHETS-FILM



Stainless Steel 30 HC/OSW

SPUTTRAD METALL

Fakta:

Transmission synligt ljus (VLT)	34%
Reflektion synligt ljus (VLR)	20%
Bländningsreduktion	62%
Solfaktor (SF)	0.53
UV-reduktion (300-380 nm)	98%
Total solenergireduktion (T _{SER})	54%
Tjocklek på film	2 mil/0,05 mm

Key Features:

- Removes up to 98% of Ultra Violet Radiation, reducing fading of fabrics, furnishing and fixtures.
- Scratch resistant coating (Durogard®) for long life and ease of cleaning.
- Ideal for office and most commercial applications.
- Provides two way mirror type privacy during day light hours.
- Improves productivity in workplace by cutting excessive solar heat.
- Reduces glare to ease eyestrain.
- Pressure sensitive adhesive with lower visual distortion and provides good optical clarity.



Montagerekommendation

HC
insides
montage

Enkelglas	Kopplade	2-glas isoler	3-glas isoler
Invändigt	Mellanglas	Ej	Ej

OSW
utsides
montage

Enkelglas	Kopplade	2-glas isoler	3-glas isoler
Utvändigt	Utvändigt	Utvändigt	Utvändigt

GARANTI: Bekaert ger 10 års fabriksgaranti på den insides installerade fastighetsfilmen (HC) och 3 år på den utsides monterade fastighetsfilmen (OSW) på vertikala glasytor.